



# DURALEX

## PRODUCT INFORMATION SHEET

### Bright Aluminium

#### DESCRIPTION

**Duralex Bright Aluminium** is an industrial grade oil based high gloss enamel for decorative and protective purposes.

#### USES

For protecting and decorating interior and exterior surfaces. Ideally suited for sheet metal roofing where a rust inhibiting finish is required.

#### SURFACE PREPARATION

Clean surface thoroughly and remove all grease, oil and grime.

**Timber:** Prime all bare timber with 2 coats of **Duralex 3in1 Primer** as per the directions on the label.

**Steel and Wrought Iron:** Remove all rust scale with a wire brush or grinder. Treat surface rust with **Duralex rustCONVERT** as per the instructions. Prime the surface with **Duralex metalPRIME** as per the directions on the label.

**Galvanised Iron and Aluminium:** Wash galvanised surfaces with mineral turps and a scourer to remove the protective film. Apply **Duralex metalPRIME** as per the instructions.

**Previously Painted Surfaces:** Ensure the surface is sound before painting. Remove all loose and flaking paint. Lightly sand the surface to a smooth and flat finish. Apply one coat of **Duralex Bright Aluminium** followed by two coats of **Duralex primeALL** as per the directions on the label.

**Thinning:** Thinning is not recommended unless applying with a spray gun, and then only thin up to 10% with mineral turps.

#### APPLICATION

Stir thoroughly before and during use with a flat broad paddle. Apply two coats with a good quality brush, or short nap roller, or spray gun (513 Spray Tip recommended).

#### DRYING TIME

In average weather conditions (25°C), touch dry in 3 hours and recoat after 24 hours. Do not apply if the temperature will be below 10°C or above 30°C during the drying time. Do not apply if rain or dew is likely within 24 hours. Cold temperatures and moisture during the drying time can result in a dull finish or the paint film running down the surface.

#### NOTES

**Duralex Bright Aluminium** is drinking water safe but

downpipes need to be disconnected from the tank until after the first good rain after the drying and curing time.

#### CLEAN UP

Do not pour leftover paint down the drain. Wash all equipment with turps. Any dried spots may be removed using turps and a clean cloth.

**Note:** Never allow waste paint to enter storm water drains or sewers.

#### COLOURS

Bright Aluminium.

#### CAUTION

Allow adequate cross ventilation when using indoors during and after use to dissipate solvent vapour.

#### SIZES

20, 10, 4 and 1 Litre.

#### RECYCLE

This container is recyclable. Please dispose of in appropriate bin.

#### IMPORTANT

Keep out of reach of children. If contact with the eyes occurs, rinse with running water and seek help if irritation persists. If swallowed, do not induce vomiting. Give a glass of water and seek medical assistance or contact the Poison Information Centre (13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Duralex product for their particular purposes. This information is being constantly updated and subject to change without notice.

CDR-363

**DURALEX**  
ENVIRONMENTALLY  
AWARE

Page 1 of 2

Once printed, this document is uncontrolled.

3-5 Muriel Avenue, Rydalmere N.S.W. 2116  
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.duralexpaints.com.au

30/10/2018

# **NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN**

## **CLEANING UP AFTER PAINTING**

### **EXCESS/UNWANTED PAINT**

- At the completion of a painting job, pour, brush or roll excess unwanted paint onto an absorbent material such as kitty litter, old rags, newspaper, cardboard, etc.
- Allow paint to dry, this could take up one week, then dispose with household waste collection services.

### **CLEAN UP:**

- Do not pour leftover paint down the drain. Wash all equipment with turps. Any dried spots may be removed using turps and a clean cloth.

**Note:** Never allow waste paint to enter storm water drains or sewers.

### **DISPOSAL OF RESIDUE:**

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.

### **CAUTION:**

- Never allow waste paint to enter household storm water drains or sewers.

## **DISPOSAL OF LEFTOVER PAINT CONTAINERS**

### **EMPTY OUT CONTAINER**

Ensure paint container is as clean as possible.

### **RECYCLE STEEL CONTAINER**

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).