



DURALEX®

Timber Care

PRODUCT INFORMATION SHEET

clean&BRIGHT CONCENTRATE 3in1 Timber Restorer

POISON

**KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING**

DESCRIPTION

DURALEX clean&BRIGHT cleans and rejuvenates bare new and old timber and prepares timber for coating by removing dirt, oils and grease and other contaminants in timber. Particularly useful for weathered timber, it gently helps to remove the surface to reveal new bright timber. Economic to use, 1 Litre is mixed with 4 Litres of water. Simply apply to entire deck or surface and let **DURALEX clean&BRIGHT** work its magic!

USES

Excellent for cleaning large areas such as decks quickly, before coating or recoating. Will remove not just dirt but aged timber fibres and any lichen, moss or algae. Formulated with an algacide, it will also gently clean algae contaminated concrete.

CAUTION should be taken around children and animals as **DURALEX clean&BRIGHT** is acid based. Care should also be taken around garden plants so have a hose ready for those little splashes or emergencies. Do not apply in the heat of the day in full sun as the **DURALEX clean&BRIGHT** may dry too quickly and not have time to clean your project. Always wear gloves and safety glasses during use.

SURFACE PREPARATION

Surface should be swept or brushed free of dirt or dust before application of **DURALEX clean&BRIGHT**.

APPLICATION:

Mix **DURALEX clean&BRIGHT** in a plastic bucket or watering can as per instructions on the label. Apply with a scrubbing brush or stiff broom. Work thoroughly into timber, working along the grain. Leave for 15-20 minutes and then rinse off with fresh, clean water. Do not leave for longer than 15 minutes on soft timbers as the grain will become 'fuzzy'. Allow to dry thoroughly before lightly sanding if necessary, and coating with your chosen top coat.

To test whether your project is ready for top coating, apply a few drops of water to the timber. If it soaks in it is clean and ready, if it beads on the surface, apply a second application of **DURALEX clean&BRIGHT**.

DRYING TIME

Drying time is dependent on the weather conditions at the time, the porosity of the timber and whether it is a vertical or horizontal surface.

To test if project is dry enough to top coat, apply a piece of plastic to the timber surface and seal. If water droplets collect under the plastic, the project is not dry enough and allow more time before top coating.

COVERAGE

1 Litre of **DURALEX clean&BRIGHT** mixed with 4 Litres of water will clean 5-10m² of timber.

CLEAN UP

Clean up tools with plenty of water. Spray vegetation with water if there is a chance of contamination. Rinse timber well with fresh water before allowing children and animals into area.

SIZES

1Ltr, 5Ltr.

RECYCLE

This container is recyclable. Please dispose of in appropriate bin.

ENVIRONMENT

Low odour. Low V.O.C. Environmentally friendly.

IMPORTANT

POISON

KEEP OUT OF REACH OF CHILDREN

READ SAFETY

DIRECTIONS BEFORE

OPENING AND USING.

Should poisoning occur

phone the Poison

Information Centre

(13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each DuraLex product for their particular purposes. This information is being constantly updated and subject to change without notice.

DURALEX
ENVIRONMENTALLY
AWARE

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.duralexpaints.com.au

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

(Industry standard for Water-based paint)

EXCESS/UNWANTED PAINT

- At the completion of a painting job, pour, brush or roll excess unwanted paint onto an absorbent material such as kitty litter, old rags, newspaper, cardboard, etc.
- Allow paint to dry, this could take up one week, then dispose with household waste collection services.

WASHING OF EQUIPMENT: (Two-Container Method)

- **20 Litre containers are best!**
- Wash brushes, rollers and other equipment in the **FIRST** container of water.
- Transfer the washed equipment to the **SECOND** container filled with clean water for a final rinse.
- Allow the containers to stand, overnight the paint solids will settle to the bottom, this usually takes about 12 hours. The clear water from the **FIRST** container may now be poured on the garden where it will be absorbed into the ground. Avoid areas near drains, streams, rivers or lakes.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The **SECOND** container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste water to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).