



DURALEX®

Timber Care

PRODUCT INFORMATION SHEET

OUTDOOR FURNITURE OIL

DESCRIPTION and USES

DURALEX OUTDOOR FURNITURE OIL can be used on new and previously oiled or stained exterior timber surfaces. Containing both linseed oil and hard wax, it will enhance the natural colour of timber as well as protect it.

SURFACE PREPARATION

Clean surface thoroughly and remove all stains, grease, dirt and mildew with **Duralex clean&BRIGHT**. Allow to dry thoroughly.

APPLICATION

Stir thoroughly with a flat paddle before and during use. Apply 2 to 3 coats with a good quality brush or clean cloth. Apply the first coat liberally to the entire surface, paying particular attention to the end grains and exposed edges. Allow the oil to soak into the timber for several minutes before going over again with a cloth rag* to remove any excess oil. Apply a second coat and again remove any excess oil. Do not apply additional coats if the surface is still tacky. For extra protection, apply a light third coat.

DRYING TIME

In average weather conditions (25°C), touch dry in 6-8 hours and recoat after 24 hours. Do not apply in temperatures below 10°C or if rain or dew is likely within 24 hours.

NOTE

Thinning of **DURALEX OUTDOOR FURNITURE OIL** is not needed nor recommended.

COVERAGE

DURALEX OUTDOOR FURNITURE OIL will cover from 6-10m² per coat per litre depending on surface conditions and application methods.

MAINTENANCE OF TIMBER SURFACE

A fresh coat of **DURALEX OUTDOOR FURNITURE OIL** can be applied as required. Clean and apply one or two coats as needed.

CLEAN UP

Clean equipment with mineral turps immediately after use.

COLOURS

Available in a range of colours including Hardwood, Redwood, Teak, Jarrah, Merbau and Natural.

DISPOSAL

Do not dispose of **DURALEX OUTDOOR FURNITURE OIL** in drains or sewers. Excess oil should be brushed out on newspaper, allowed to dry and disposed of through the normal waste collection. (See Product Information Sheet for disposal).

SIZES

250mL, 500mL and 1 Ltr.

RECYCLE

This can is recyclable. Check with your local council to see if it is participating in a steel can recycling program.

ENVIRONMENT

This product is regulated as Class 3 Dangerous Goods, packing group III.



SAFETY

Provide adequate ventilation during use and drying time. Keep **DURALEX OUTDOOR FURNITURE OIL** out of reach of children. If contact with the eyes occurs, rinse with running water and seek help if irritation persists. If swallowed, do not induce vomiting. Give a glass of water and seek medical assistance or contact the Poison Information Centre (13 11 26).

*Linseed Oil is an exothermic oil and can self ignite when left in oily rags. All rags used should be washed in soapy water and dried before being stored or disposed of.



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Duralex product for their particular purposes. This information is being constantly updated and subject to change without notice.

DURALEX
ENVIRONMENTALLY
AWARE

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.duralexpaints.com.au

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

EXCESS / UNWANTED PAINT & RESIDUE

- At the completion of a painting job, brush out excess unwanted oil onto newspaper, allow to dry and dispose of through the normal waste collection. (See Product Information Sheet for disposal).

WASHING OF EQUIPMENT:

- Clean equipment with mineral turps immediately after use.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The SECOND container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste product to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).