



DURALEX®

Timber Care

PRODUCT INFORMATION SHEET

dura-FILL®

DESCRIPTION

DURALEX dura-FILL® is an interior/exterior multi purpose filler for knots, holes, cracks and blemishes. It is simple to use, dries quickly and will not shrink or crack. It is easy to sand and will not clog sand paper. Drying to a pale grey colour, it is most suitable under painted finishes. Application is easy with a putty knife, spatula or even your finger.

USES

Use **DURALEX dura-FILL®** for all knots, holes, cracks in timber, plasterboard and small masonry defects. Suitable for interior and exterior applications. Ideal for under painted surfaces, it can be sanded, drilled and nailed when fully dry.

SURFACE PREPARATION

ALL SURFACES INCLUDING NEW BARE TIMBER, OLD BARE TIMBER, PREVIOUSLY STAINED SURFACES AND PREVIOUSLY PAINTED SURFACES: The surface to be filled must be thoroughly dry, free of oil and wax.

Remove any flaking paint from surrounding area before filling with **DURALEX dura-FILL®**.

APPLICATION

Duralex dura-FILL® can be applied straight from the container with a putty knife or for smaller jobs, applied or smeared with your fingers. Apply a little more than you need to fill the defect and simply sand off excess with sandpaper when it is dry and hard to touch. Shallow grooves, cracks and scratches can be filled with your finger and the excess simply wiped away before a light sand when dry. Filled areas can be painted immediately after sanding smooth.

DRYING TIME

Drying time is a little dependent on the ambient temperature. Only apply **Duralex dura-FILL®** when surface temperature is above 10°C and below 30°C. **Duralex dura-FILL®** will be touch dry in 30mins and able to be sanded in 45 mins in most cases. Some large areas may need longer drying time

COVERAGE

DURALEX dura-FILL® will fill 1:1 with the size of the container purchased.

CLEAN UP

Clean equipment and hands with warm soapy water. Should spills occur, simply scoop up and discard.

CAUTION

Allow adequate cross ventilation when painting indoors during and after use to dissipate water vapour.

COLOURS

Available in natural grey.

SIZE

75mL, 125mL.

ENVIRONMENT

Low odour. Low V.O.C. Environmentally friendly.

IMPORTANT

Keep out of reach of children. To avoid spoilage of filler keep container sealed when not in use.

Poison Information Centre (13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Duralex product for their particular purposes. This information is being constantly updated and subject to change without notice.

DURALEX
ENVIRONMENTALLY
AWARE

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.duralexpaints.com.au

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

(Industry standard for Water-based paint)

EXCESS/UNWANTED PAINT

- At the completion of a painting job, pour, brush or roll excess unwanted paint onto an absorbent material such as kitty litter, old rags, newspaper, cardboard, etc.
- Allow paint to dry, this could take up one week, then dispose with household waste collection services.

WASHING OF EQUIPMENT: (Two-Container Method)

- **20 Litre containers are best!**
- Wash brushes, rollers and other equipment in the **FIRST** container of water.
- Transfer the washed equipment to the **SECOND** container filled with clean water for a final rinse.
- Allow the containers to stand, overnight the paint solids will settle to the bottom, this usually takes about 12 hours. The clear water from the **FIRST** container may now be poured on the garden where it will be absorbed into the ground. Avoid areas near drains, streams, rivers or lakes.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The **SECOND** container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste water to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).