



DURALEX

PRODUCT INFORMATION SHEET

RENOVATOR LOW SHEEN

DESCRIPTION

Duralex Renovator Low Sheen is a budget quality, acrylic wall and ceiling house paint which dries to a tough finish on appropriate and properly prepared interior and exterior surfaces.

This product has a sheen rating of approximately 5% compared to a flat which is about 1.7%.

USES

Ideally suited for walls and ceilings.

SURFACE PREPARATION

BEFORE PAINTING: Ensure surface is firm, properly prepared, thoroughly dry, dust free, clean and free of all foreign matter. If necessary, fill all nail holes, cracks, etc. with a suitable filler, sand smooth and dust down.

Efflorescence or mould on any surface must be treated first.

Brick, Masonry, Fibro, Gyprock, etc.

New unpainted – Remove dust, loose sand, etc. especially from cement render by rubbing with a block of oregon timber and sweep clean. Apply one coat of **Duralex Renovator Undercoat & Wallboard Sealer** followed by two coats of **Duralex Renovator Low Sheen**.

Exterior Timber

New unpainted - **Duralex Renovator Low Sheen** is not recommended for use on exterior timber. In these areas one coat of **Duralex 3in1 Primer Undercoat** followed by two coats of **Duralex Sun Master Gloss or Sun Master Low Sheen**, is recommended.

Previously Painted Surfaces

Before recoating previously painted surfaces, ensure that the surface is firm. Unsound surfaces should be stripped before repainting to achieve the best results. Test at random for its ability to withstand extra coats. Simply cut a small cross (x) through the paint with a razor blade, then place a piece of sticky tape firmly over the cut. Hold the side of the tape then rip the tape off. If the tape pulls the surface away, the surface is unsound. Test different areas before deciding whether or not the surface coating should be removed. After removing all loose, flaking paint and powdery deposits, apply **Duralex Surface Binder** where necessary. Sand glossy surfaces to provide a key. Prime any bare interior timber or rust-prone metal surfaces with **Duralex 3in1 Primer Undercoat** and rust-prone metal surfaces with a suitable primer. Apply two coats of **Duralex Renovator Low Sheen**.

APPLICATION

Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action. To ensure

best performance, do not use any additive not approved by Duralex. Avoid excessive brushing or roller pressure and disturbing freshly laid paint which has begun to dry. Do not overspread.

Thinning with up to 10% water may be necessary when painting outside during hot weather or when painting highly absorbent surfaces, or if ropiness or roller stipple is experienced.

NOTE: If stopping for a short break, insert paint and roller in a plastic bag to avoid paint drying out. This will provide for a smoother, nib free job.

DRYING TIME

Normally dries in 20 minutes in dry, well ventilated areas and may be recoated after 2 hours. In damp or humid conditions drying time is lengthened – Remember ventilation is important.

WEATHER

Surface temperature must be above 10°C during application and drying time. **Duralex Renovator Low Sheen** must be at least two hours dry before dew, fog or rain when used outside.

COVERAGE

A maximum coverage rate of 16 square metres per Litre. This may fall below 10 square metres per Litre when painting corrugated, rough or absorbent surfaces.

CLEAN UP

Wash all equipment with clean water. Any dried spots may be removed using methylated spirits.

COLOURS

Available in White & Bases, which are compatible with all major tinting systems. Tinter, if added, should be shaken and stirred in thoroughly immediately after addition.

CAUTION

Allow adequate cross ventilation when painting indoors during and after use to dissipate water vapour.

SIZES

20, 10, 6, 4 Litre.

ENVIRONMENT

Low odour. Low V.O.C.
Environmentally friendly.

IMPORTANT

Keep out of reach of children. To avoid spoilage of paint keep container sealed when not in use. Poison Information Centre (13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Duralex product for their particular purposes. This information is being constantly updated and subject to change without notice.

DURALEX
ENVIRONMENTALLY
AWARE

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.duralexpaints.com.au

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

(Industry standard for Water-based paint)

EXCESS/UNWANTED PAINT

- At the completion of a painting job, pour, brush or roll excess unwanted paint onto an absorbent material such as kitty litter, old rags, newspaper, cardboard, etc.
- Allow paint to dry, this could take up one week, then dispose with household waste collection services.

WASHING OF EQUIPMENT: (Two-Container Method)

- **20 Litre containers are best!**
- Wash brushes, rollers and other equipment in the FIRST container of water.
- Transfer the washed equipment to the SECOND container filled with clean water for a final rinse.
- Allow the containers to stand, overnight the paint solids will settle to the bottom, this usually takes about 12 hours. The clear water from the FIRST container may now be poured on the garden where it will be absorbed into the ground. Avoid areas near drains, streams, rivers or lakes.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The SECOND container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste water to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).