



DURALEX

PRODUCT INFORMATION SHEET

SQUASH COURT

DESCRIPTION

Duralex SQUASH COURT is a professional quality water-based paint which dries to a flat finish on properly prepared interior and exterior surfaces.

Independent field testing, where squash balls were fired at test panels of various manufacturer's paints, found that **Duralex SQUASH COURT** was noticeably superior.

USES

Duralex SQUASH COURT is especially formulated for playing area walls where high levels of adhesion and scuff/wear balance is important so that minimal marking of wall and ball occurs.

SURFACE PREPARATION

BEFORE PAINTING: Ensure surface is firm, properly prepared, thoroughly dry, dust free, clean and free of all foreign matter.

Previously painted Surfaces

Prior to commencement of the recoating of previously painted surfaces, random tests for soundness should be conducted. Small crosses (x) should be made through the paint film using a razor blade, adhesive tape should be placed over the crosses and removed in a single motion. Should the paint film adhere to the adhesive tape the surface is deemed to be unsound.

Unsound Surfaces

After removing all loose, flaking paint and powdery deposits apply **Duralex SURFACE BINDER** followed by two coats of **Duralex SQUASH COURT**.

Cement Render, Brick, Cement Blocks, Gyprock, etc.

New Unpainted - Remove all dust, contaminants, etc. To remove loose sand from cement render rub with timber block and sweep clean.

New Unpainted "Tilt-Up" concrete walls are coated with invisible bond-breaker release chemicals which prevent paint adhesion if not removed. We suggest a product such as TiltWash or similar, be used according to manufacturer's directions. Tilt-Up bond breaking chemicals and Sugar Soap are highly alkaline (caustic). They must be thoroughly rinsed off prior to painting.

Apply one coat of **Duralex 3in1 PRIMER UNDERCOAT** followed by two coats of **Duralex SQUASH COURT**.

Gloss surfaces must be sanded to provide a key. Prime all bare timber and rust resisting bare metals with **Duralex 3in1 PRIMER UNDERCOAT**. Rust prone metals should be rendered rust resistant with a suitable primer.

APPLICATION

Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action.

Thinning with up to 10% water may be necessary when painting highly absorbent surfaces.

DRYING TIME

Normally dries in 20 minutes in a well ventilated area and may be recoated in 2 hours. Court may be played on next day. Damp, humid conditions may lengthen drying time.

COVERAGE

A maximum coverage rate of 16 square metres per Litre per coat. Approximately 20 Litres per court using 2 coats.

CLEAN UP

Wash all equipment and spills with clean water. Any dried spots may be removed using methylated spirits.

WEATHER

Surface temperature must be above 10°C and below 35°C during application and drying time. **Duralex SQUASH COURT** must be at least two hours dry before dew, fog or rain when used outside.

CAUTION

Allow adequate cross ventilation when painting indoors during and after use to dissipate water vapour.

SIZES

20 Litre only.

ENVIRONMENT

Low odour. Low V.O.C. Environmentally friendly.

IMPORTANT

Keep out of reach of children. To avoid spoilage of paint keep container sealed when not in use. Poison Information Centre (13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Duralex product for their particular purposes. This information is being constantly updated and subject to change without notice.

CDR-4-099

DURALEX
ENVIRONMENTALLY
AWARE

Page 1 of 2

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.duralexpaints.com.au

8/4/14

Once printed, this document is uncontrolled.

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

(Industry standard for Water-based paint)

EXCESS/UNWANTED PAINT

- At the completion of a painting job, pour, brush or roll excess unwanted paint onto an absorbent material such as kitty litter, old rags, newspaper, cardboard, etc.
- Allow paint to dry, this could take up one week, then dispose with household waste collection services.

WASHING OF EQUIPMENT: (Two-Container Method)

- **20 Litre containers are best!**
- Wash brushes, rollers and other equipment in the FIRST container of water.
- Transfer the washed equipment to the SECOND container filled with clean water for a final rinse.
- Allow the containers to stand, overnight the paint solids will settle to the bottom, this usually takes about 12 hours. The clear water from the FIRST container may now be poured on the garden where it will be absorbed into the ground. Avoid areas near drains, streams, rivers or lakes.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The SECOND container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste water to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).