



DURALEX[®]

Premium Paint since 1946

TRIM MASTER[®]



Water based enamel paint suitable for interior and exterior windows, doors, trims and skirting boards. Superior cross-linking 100% acrylic technology resulting in a harder, tougher surface coating

available in 500mL, 1, 2, 4 and 10 Litre sizes



Durablex Paints Pty Ltd, 3-5 Muriel Ave, RYDALMERE NSW 2116 www.durablexpaints.com.au

tel: 02) 9638 0568

fax: 02) 9684 1864

email: sales@durablexpaints.com.au

NON-STICK RESISTANCE TESTS CONDUCTED IN ACCORDANCE TO:

Australian Standard AS 1580.409.3 - 2002

The test is designed to simulate the painting of windows through summer. When painted, windows are usually allowed to remain open overnight to dry before closing the following night. This ensures sufficient time is allowed for drying and to prevent the sliding window from sticking to the window frame.

The test itself involves priming and gloss top coating two pieces of 4cm wide timber panels and allowing to dry overnight at room temperature. The timber panels are placed face to face and lying flat, so the painted surfaces are in direct contact. A weight of 1kg is placed directly over the test area. The testing material is placed into a pre-heated chamber for 60 minutes set to 50°C. The test panels are then removed and allowed to cool. A moderate twisting force is applied to separate the panels and examined for any paint surface damage and deformation.

PHOTO OF TEST PANELS



Marks on the panels above show the extent of damage occurring on each product tested.