



DURALEX

PRODUCT INFORMATION SHEET

BLOCK & RENDER FILLER

DESCRIPTION

Durablex BLOCK & RENDER FILLER is an acrylic interior/ exterior filler for ROUGH surfaces.

USES

Durablex BLOCK & RENDER FILLER is formulated for use on previously unpainted rough cement blocks and coarse cement render.

It is not intended for smooth, waterproof or dense in-situ concrete or permanently damp surfaces.

SURFACE PREPARATION

BEFORE PAINTING: Ensure surface is firm, properly prepared, thoroughly dry, dust free, clean and free of all foreign matter. If necessary, fill all holes, cracks, etc. with a suitable filler.

Efflorescence or mould on any surface must be treated first. Remove dust, loose sand etc. especially from cement render by rubbing with a block of timber and sweep clean.

Allow new cement render to cure at least four weeks prior to application of **Durablex BLOCK & RENDER FILLER**.

APPLICATION

IMPORTANT: Wet brush or roller in water and shake off excess prior to use, for a smoother, nib free job. Do not overspread.

Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action. To ensure best performance, do not use any additive not approved by Durablex. Avoid excessive brushing or roller pressure and disturbing freshly laid filler which has begun to dry.

Do not thin **Durablex BLOCK & RENDER FILLER** except when painting outside in hot, dry conditions, when a maximum addition of 10% water may be used.

Allow a minimum of 2 hours to dry before applying two coats of finishing paint.

COVERAGE

A maximum coverage rate of 12 square metres per Litre per coat. This may reduce when painting corrugated, rough or absorbent surfaces.

CLEAN UP

Wash all equipment and spills with clean water. Any dried spots may be removed using methylated spirits.

WEATHER

Surface temperature must be above 10°C and below 35°C during application and drying time. **Durablex BLOCK & RENDER FILLER** must be at least two hours dry before dew, fog or rain when used outside.

COLOURS

Available in White, which is compatible with all major tinting systems. Tinter, if added, should be shaken and stirred in thoroughly immediately after addition.

To obtain light tint colours use only one third to one half the normal amount of tinters.

CAUTION

Allow adequate cross ventilation when painting indoors during and after use to dissipate water vapour.

SIZES

20 Litre.

ENVIRONMENT

Low odour. Low V.O.C. Environmentally friendly.

IMPORTANT

Keep out of reach of children. To avoid spoilage of paint keep container sealed when not in use. Poison Information Centre (13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Durablex product for their particular purposes. This information is being constantly updated and subject to change without notice.

DURALEX
ENVIRONMENTALLY
AWARE

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.durablexpaints.com.au

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

(Industry standard for Water-based paint)

EXCESS/UNWANTED PAINT

- At the completion of a painting job, pour, brush or roll excess unwanted paint onto an absorbent material such as kitty litter, old rags, newspaper, cardboard, etc.
- Allow paint to dry, this could take up one week, then dispose with household waste collection services.

WASHING OF EQUIPMENT: (Two-Container Method)

- **20 Litre containers are best!**
- Wash brushes, rollers and other equipment in the FIRST container of water.
- Transfer the washed equipment to the SECOND container filled with clean water for a final rinse.
- Allow the containers to stand, overnight the paint solids will settle to the bottom, this usually takes about 12 hours. The clear water from the FIRST container may now be poured on the garden where it will be absorbed into the ground. Avoid areas near drains, streams, rivers or lakes.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The SECOND container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste water to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).