



DURALEX®

Timber Care

PRODUCT INFORMATION SHEET

WATER BASED OUTDOOR FURNITURE OIL

DESCRIPTION and USES

DURALEX WATER BASED OUTDOOR FURNITURE OIL is an acrylic coating that comes in a range of appealing, transparent timber colours.

Water repellent, it will condition timber as it protects, will not flake or peel and is easy to recoat without onerous preparation.

Excellent for all exterior timbers from hand rails, furniture, pergolas, fences and window frames.

PREPARATION

ALL SURFACES INCLUDING NEW BARE TIMBER, OLD BARE TIMBER, PREVIOUSLY STAINED SURFACES AND PREVIOUSLY PAINTED SURFACES:

To test whether your project is ready to accept **DURALEX WATER BASED OUTDOOR FURNITURE OIL**, apply a sprinkle of water to the surface. If it soaks in, it is clean and ready; if it beads on the surface it is not ready. To accelerate weathering apply **DURALEX clean&BRIGHT CONCENTRATE 3in1 Timber Restorer** as per label instructions. The surface to be coated must be thoroughly dry, free of oil and wax and be well sanded. Sand with 150 grit for best results. Always sand in the direction of the grain. Remove all dust, wipe down with a damp, lint free cloth and allow to dry. Cracks, holes and knots should be filled with a suitable wood filler and allowed to dry. To refresh timber that has been previously painted with **DURALEX WATER BASED OUTDOOR FURNITURE OIL** simply wash with soapy water, rinse and allow to dry. Recoat with chosen colour.

APPLICATION

Application can be made with brush, roller or painters pad. Apply with smooth even strokes, along the grain of the timber. Do not apply in the full sun or in the middle of the day. Best to apply in the morning after any dew or rain has dried. Two generous coats are recommended to bare timber but apply a third coat if the timber appears patchy.

DRYING TIME

Drying time is dependent on the ambient temperature. Only apply **DURALEX WATER BASED OUTDOOR FURNITURE OIL** in temperatures above 10°C and below 30°C. Coating will be touch dry in 30 mins and able to be recoated in 2 hours.

COVERAGE

DURALEX WATER BASED OUTDOOR FURNITURE OIL will cover from 6-10m² per coat per litre depending on

surface conditions and application methods.

CLEAN UP

Clean equipment and spills with water immediately after use. Use Methylated Spirits for dried spots.

COLOURS

Available in a range of colours including Hardwood, Redwood, Teak, Jarrah, Merbau and Natural.

IMPORTANT NOTES & DISPOSAL

Paint container must be properly sealed at all times when not in use. Do not pour leftover product down drain. Wash all equipment with clean water. (See Product Information Sheet for disposal).

Note: Never allow waste water to enter storm water drains or sewers.

SIZES

250mL, 500mL and 1 Ltr.

RECYCLE

This can is recyclable. Check with your local council to see if it is participating in a steel can recycling program.

SAFETY

Keep out of reach of children. If contact with the eyes occurs, rinse with running water and seek help if irritation persists. If swallowed, do not induce vomiting. Give a glass of water and seek medical assistance or contact the Poison Information Centre (13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Durablex product for their particular purposes. This information is being constantly updated and subject to change without notice.

DURALEX
ENVIRONMENTALLY
AWARE

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.durablexpaints.com.au

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

EXCESS / UNWANTED PAINT & RESIDUE

- At the completion of a painting job, brush out excess unwanted oil onto newspaper, allow to dry and dispose of through the normal waste collection. (See Product Information Sheet for disposal).

WASHING OF EQUIPMENT:

- Clean equipment with water immediately after use.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The SECOND container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste product to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).